

SMART Pallet Station lift 600

Product number | RI-00502



Max Payload

600 kilo

Capacity

20/h

Compatible

KMP 1500P
KMP 600P

Features

- Various delivering height
- Single EU pallet handling
- Sensor for pallet detection
- HMI for status and setup
- Comm OPCUA, TCP, I/O
- Easy installation
- Easy integration
- Safe operation



PURCHASE INFORMATION

Product number	RI-00502 Smart Pallet Station lift 600
Option 1	RI-00511 Spacers



GENERAL INFORMATION

Type	Smart Pallet Station lift 600 kilo
Color	RAL7021 Fine Structure
Cover material	Powder painted
Product design life	5 years

COMPATIBLE

KMP 1500P	Spacers
KMP 600P	Spacers

DIMENSIONS

Length	1478 mm $\pm$ 3 mm
Width	1368 mm $\pm$ 3 mm
Height	925 mm $\pm$ 3 mm
Height top roller	396 mm - 920 mm $\pm$ 3 mm
Weight	380 kilo

PAYLOAD

Maximum payload	600 kilo
Maximum payload pr roller	50 kilo
Standard EU Pallets	1200 x 800 x 144 mm

LIFTING HEIGHT

Variable	
Minimum	396 mm
Maximum	920 mm

ROLLER SPEED

Default	0,09 m/s
Min speed	0,1 m/s
Max speed	0,17 m/s

CAPACITY

20/h Depends on the AMR load operation and fleet management.

ENVIROMENT

IP	4x
Ambient temprature range	5°C to 40°C
Humidity	10-95% non-condensing

SAFETY

Sil 1	
Emergency stop	3 pcs
Service Switch	Maintenance

POWER

Voltage	120-260 VAC
Current	Max 16 Amp
Frequency	50-60 Hz
Phase	1
Watt	1000W

HMI | CONTROL PANEL

Mounting	On frame. Max distance from station 5000mm
Length	600mm
Width	600mm
Height	1700mm
Display	Operation interface



COMMUNICATION

OPCUA
TCP
I/O

APPROVAL

CE approved and compliant with 2006/42/EC machinery directive.